



3 KERN KIP-V20M

Weighing bridge



- Weighing bridge with non-slip chequer plate, lacquered, welded
- 4 Load cells, steel, silicone-coated, IP67, OIML-R60-approval for verification, class III, 3000 e
- Can be built in using pit frames (optional)
- Level indicator and levelling feet for precise levelling of the scale
- Easy access to the junction box from the top
- Comfortable levelling of the weighing bridge from the top
- Accessories see KERN BID, page 105/106

4 KERN KFP-V20 IP67

Weighing bridge



- **C** Weighing plate screwed on from the top (models with [Max] ≤ 1500 kg), so it easy to remove, hygienic and easy to clean.
- Lacquered steel weighing bridge, weighing plate size 1500×1500×130 mm corrugated steel plate. Extremely resistant to bending due to material thickness
- 4 Load cells, steel, silicone-coated, IP67, OIML-R60-approval for verification, class III, 3000 e
- Can be built in using pit frames (optional)
- Level indicator and levelling feet for precise levelling of the scale
- Easy access to the junction box from the top
- Comfortable levelling of the weighing bridge from the top
- Accessories see KERN BFB, page 107/108

5 KERN KFD-V20

Weighing bridge



- Weighing bridge made of non-slip corrugated steel plate, lacquered, two access ramps integrated, extremely resistant to bending
- Extremely flat construction to facilitate access: access height only 45 mm
- 4 Load cells, alloy steel, silicone-coated, IP67, OIML-R60-approved class III, 3000 e
- Accessories see KERN NFB page 116



Model	Weighing range [Max] kg	Readability [d] g	Verification value [e] g	Min. load [Min] g	Cable length approx. m	Net weight approx. kg	Weighing plate W×D×H mm	Price excl. VAT, ex works €
3 Weighing bridge KIP-V20M								
KIP 600V20SM	600	200	200	4000	5	130	1000×1000×108	980,-
KIP 600V20M	600	200	200	4000	5	150	1500×1200×108	1310,-
KIP 1500V20SM	1500	500	500	10000	5	130	1000×1000×108	1140,- [Ⓢ]
KIP 1500V20EM	1500	500	500	10000	5	140	1200×1000×108	1070,-
KIP 1500V20M	1500	500	500	10000	5	150	1500×1200×108	1310,- [Ⓢ]
KIP 3000V20M	3000	1000	1000	20000	5	150	1500×1200×108	1310,-
KIP 3000V20LM	3000	1000	1000	20000	5	180	1500×1500×108	1560,-
4 Weighing bridge KFP-V20 IP67								
KFP 600V20SNM	600	200	200	4000	5	105	1000×1000×80	1220,-
KFP 600V20NM	600	200	200	4000	5	135	1500×1250×80	1760,-
KFP 1500V20SNM	1500	500	500	10000	5	105	1000×1000×80	1260,-
KFP 1500V20NM	1500	500	500	10000	5	135	1500×1250×90	1730,-
KFP 3000V20NM	3000	1000	1000	20000	5	135	1500×1250×90	1760,-
KFP 3000V20LNM	3000	1000	1000	20000	5	155	1500×1500×80	1960,-
KFP 6000V20M	6000	2000	2000	40000	5	210	1500×1500×130	2320,-
5 Weighing bridge KFD-V20								
KFD 600V20M	600	200	200	4000	5	125	1600×1200×78	1700,-
KFD 600V20LM	600	200	200	4000	5	155	1800×1400×80	2000,-
KFD 1500V20M	1500	500	500	10000	5	125	1600×1200×78	1700,-
KFD 1500V20LM	1500	500	500	10000	5	175	1800×1400×78	2000,-

[Ⓢ] Price reduction