



Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP65), with EC type approval [M]

Features

- High mobility: thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department etc.)
- **1** Load support: stainless steel, Weighing bridge can also be delivered as component without the display device, for details see KERN KFU-V30
- 4 silicone-coated steel load cells, dust and spray protection IP67
- Your support in a HACCP-compliant quality system
- Ideal for the increased hygienic requirements in the food industries
- **2** Display device: for details see KERN KFN-TM
- The scale can be easily transported using rollers and a handle and does not require much storage space
- Hold function: When the weighing conditions are unstable, a stable weight is calculated determining an average value

- Weighing with tolerance range (checkweighing): A visual and audible signal assists the rapid checking of items on pallets
- Totalising of weights
- **3** Did you know? Our floor scales are delivered in a robust wooden box. This protects the high-quality weighing technology from environmental influences and stresses during transportation. KERN – always one step ahead

Technical data

- Large backlit LCD display, digit height 52 mm
- Dimensions of display device WxDxH 266x165x96 mm
- Cable length of display device approx. 5 m
- Permissible ambient temperature -10 °C/40 °C

Accessories

- **4** Stand to elevate display device, height of stand approx. 800 mm, KERN BFN-A04, € 355,-
- Internal rechargeable battery pack, operating time up to 35 h without backlight, charging time approx. 10 h, KERN GAB-A04, € 42,-
- RS-232 data interface including interface cable, Data interface RS-232, interface cable included, approx. 1,5 m, must be ordered at purchase, KERN KFN-A01, € 220,-
- Bluetooth data interface for wireless data transfer to PC or tablets, must be ordered at purchase, not possible in combination with verification, KERN KFB-A03, € 160,-
- Analogue module 0-10 V, must be ordered at purchase, KERN KFB-A04, € 170,-
- Analogue module 4-20 mA, must be ordered at purchase, KERN KFB-A05, € 170,-
- Large display with superior display size, KERN YKD-A02, € 310,-
- Cable with special length 15 m, between display device and platform, for verified models which must be ordered at the time of purchase, KERN BFB-A03, € 198,-
- Further details, plenty of further accessories and suitable printers see *Accessories*

1 Shipment via freight forwarder. Please ask for dimensions, gross weight, shipping costs
Optionally configurable with IP68 display device on request, for details see chapter 13

STANDARD



OPTION



FACTORY



Model	Weighing capacity [Max] kg	Readability = Verification value [d] = [e] kg	Verification value [e] kg	Minimal load [Min] kg	Net weight approx. kg	Price excl. of VAT ex works €	Option			
							Verification KERN €	DAkkS KERN €	Calibr. Certificate €	
KERN UFN 600K200IPM	600	0,2	0,2	4	55	2000,-	965-230	150,-	963-130	196,-
KERN UFN 1.5T0.5IPM	1500	0,5	0,5	10	50	2000,-	965-230	150,-	963-130	196,-

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.
Verification at the factory, we need to know the full address of the location of use.